



## 2019 Electric Urban Cab Over

<b>Dimensions</b>	Wheelbase (in/mm)	130 / 3,300
	Overall Length (in/mm)	236 / 5,995
	Cabin Width Excluding Mirrors (in/mm)	74.4 / 1890
	Overall Height (in/mm)	112.2 / 2,850
	Curb Weight (lb/kg)	5,732 / 2,600
	Gross Vehicle Weight Ratings (lb/kg)	[11,464 / 5,200] or [14,100 / 6,400]
<b>Mechanical</b>	Drive	RWD
	Single Motor	Synchronous Permanent Magnet
	Transmission	2 Speed
	Motor Cooling	Liquid Cooling
	Capacity / Battery Chemistry	77.8 kWh / Li-ion
	On-Board Charger	6.6kW (Overnight Charging)
<b>Performance</b>	Charger Type	J1772 CCS Level 2
	Total Peak Power (hp/kW)	161 / 120
	Total Peak Torque (lb-ft/Nm)	756 / 1025Nm
	Top Speed (mph/km/h) Max.	62 / 100
	Gradeability [%]	≥25%
	Turning Radius (ft/m)	23 / 7
<b>Body &amp; Chassis</b>	Typical Duty Cycle	Parcel Delivery Van Class 3/4
	Chassis	Ladder Frame
	Front Suspension	Leaf Spring / Disk Brakes
	Rear Suspension	Leaf Spring / Drum Brakes
	Hydraulic Brake System	ABS / EBD
	Michelin Agilis® CrossClimate®*	225 / 75R16LT
<b>Standard Features</b>	*low-rolling resistance tires maximize vehicle range	
	Air Conditioning / PTC Heating	Driver's Seat Adjustable High Back
	Tilt Telescopic Steering Column	Passenger Seat Adjustable High Back with Middle Bench Seat
<b>Enhanced Truck Features*</b>	Power Door Locks - Keyless Entry	
	Cab Air Deflector	*Studies show energy savings of 5% for a stop and start suburban route and 7% for highway route



\*Shown with optional dry freight box



**Zero Emissions, 100% Electric**

**Zero Noise Pollution**



NOTE: All specifications are with normal manufacturing allowances and tolerances. Envirotech Drive Systems Incorporated. reserves the right to alter specifications at any time without prior notice.

Copyright © 2019 Envirotech Drive Systems Incorporated. All rights reserved. - [www.envirotechvehicles.com](http://www.envirotechvehicles.com)