# Options shown in RED

#### General

45' Length Height 11'6" Width 102" Headroom 75.75" 25' 4.5" Wheelbase Underfloor Storage Capacity (w/ lift) 143 cu ft Parcel Rack Storage Capacity (w/lift) 80.5 cu ft Front Overhang 6'2.4" 9'2.2" Rear Overhang Turning Radius @ Body Corner 43'11.5"

#### **Electric Powertrain**

- Permanent Magnet Drive Motor 310kW nominal power - 360kW peak power
- Battery NMC Lithium Ion (US make)
- Energy content 648 kWh
- Range 220 miles [355 km]
- Range [Service]<sup>1</sup> 195 miles [310 km]
- Traction System Siemens ELFA II
- Rear Right Hand Side Plug-in CCS-1 DC Fast Charging Port

### Ride and Handling

- Six Wheel Disc Brakes Knorr
- Six Wheel Unitized Hubs
- ZF Variable Ratio Steering
- Independent Front & Tag Axle Suspension
- Suspension Knorr ELC
  - -Tag Axle Unloading System
  - -Rapid Rear Raise System
  - -Front Kneeling w/ Quick Recovery System
  - -Full Coach Raise & Lowering

# **Body Construction / Chassis**

- Stainless Steel Chassis, Windshield
  & Side Window Frames
- One Piece Galvanized Steel Side Walls
- One Piece Aircraft-Quality Aluminum Roof
- Aluminum Pantograph Baggage Bay Doors
- Energy Absorbing Bumpers
- Dana/Spicer S172 Drive Axle

# Electrical and Lighting

- Projector Beam Headlights
- LED Daytime Running Lights
- LED Side Marker Lamps w/ Integrated Turn Signal Function
- Full Multiplex System
- High Mount LEĎ Brake Light
- LED Interior Ceiling Aisle Lights

# E-specs shown in GREEN

### **Electrical and Lighting (Continued)**

- Front Side Cornering Lights
- LED Tail & Reverse Lights
- Dash Mounted 12/24 Volt Cut-Off Switch
- Battery Equalizer
- Easily Serviceable Tail Lights
- LCD Multi-Function Driver Display
- Automatic Entrance Lighting
- Keyless Ignition Switch
- Curb Side Lighting
- Battery Charger
- Road Side Lighting
- 110V Tamper-Resistant AC Receptacles, with or without USB

### **Tires and Wheels**

- Alcoa Dura Bright Aluminum Wheels (9)
- 315/80R-22.5 Goodyear Marathon LHS II + HL

#### Interior

- Seating:
- Max. 56 Passenger KIEL 1020 Seats w/ Footrest & 3-Point Seat Belts
- ISRI 6800/348 Adjustable Drivers Seat (Pneumatic) w/ 3-Point Seat Belt (3rd Point Fixed on B-Post)
- ISRI 6832-870 Drivers Seat w/ Integrated 3-Point Seat Belt
- Two Piece Windshield
- Double Pane Seamless Side Glass
- Enhanced Curved Entry Stairwell
- Tilt & Telescopic Steering Wheel
- Driver's Right Hand Console w/ Grab Rail
- Two Left Hand Driver Cup Holders
- Map Light
- Passenger Individual Reading Lights w/ Directional Adjustment
- Sliding Passenger Multisets
- Electric Windshield Sun Visors
- Supplemental Restroom Holding Tank
- Keyed Alike Baggage & Service Doors
- Central Air Locking System Baggage Doors
- Ramped Entry Aisle (In Lieu of Step)
- Monogram Flush Toilet
- Rear Window
- Passenger Side Window Shades
- Enclosed Parcel Racks
- Contoured Parcel Racks w/ 23" Monitors
- Magazine Nets
- Cup Holders
- Card Tables
- Driver's Shield

#### **Climate Control**

- Integrated HVAC System
- Eberspächer Sütrak
- 134a Refrigerant
- Timer for Auxiliary Heater

# **Other Equipment**

- Remote-Control & Heated Black Mirrors
- Audio System w/ PA & Two Microphones
- Touchscreen Radio w/ DVD Player & Back-up Camera Display
- Enhanced Sound System
- Cordless Microphone
- Individual Multi-Channel Audio System
- Custom Paint
- Custom Vinyl Graphics Installation
- Destination Sign(s)
- Global Positioning System
- In-Motion Satellite TV System
- Road Viewing Monitor System
- Side View Cameras
- WiFi

#### Wheelchair Lift

- Midship Wheelchair Lift Ready w/ two Tie-Down Positions
- Passenger Chime Buttons for ADA Seats
- Braun NL-501

# EXTENSIVE STANDARD SAFETY PACKAGE

- Generally manufactured in Accordance with Roll-over UN/ECE – Reg. No.66
- FMVSS 210 Seating w/ 3-Point Seat Belts
- 3-Point Seat Belt Driver Seat
- Electronic Braking System (EBS)
- Automatic Traction Control (ATC)Daytime Running Lights (DRL)
- Electronic Stability Control (ESC)
- Fire Detection System
- Tire Pressure Monitoring System (TPMS)
- Lane Departure Warning System (LDW)
- Static Aiming Light System
- Backup Camera with In-Dash Display
- Roof Hatches



<sup>&</sup>lt;sup>1</sup> Simulated range based on a suburban drive profile at an ambient temperature of 68°F (20°C), max. speed of 65 mph and fully loaded vehicle.

These specifications are based on up-to-date product information available at the time of printing December 2020. Specifications can change without prior notice.