

2024 Zevo 600 Specifications & Highlights



VEHICLE

GVWR: 9,990- or 11,000-lb. options available	Cargo volume: 614.7 cu. ft.
Exterior dimensions*: 290" x 86" x 109"	Minimum ground clearance: 7.51"
Rear cargo access dimensions: 58" x 73"	Available max payload**: 3,230 lbs.

PERFORMANCE

Peak charge rate: Up to 160 miles of range per hour (120-kW DC Fast Charging¹)

Driving range on full charge: Up to 250 miles¹

LIMITED WARRANTIES

3 years, 36K miles Bumper to Bumper²

8 years, 100K miles Electrification²

6 years, 100K miles Corrosion Coverage²



SAFETY

Over 20 available safety and driver assistance features, including:

- | | | | | |
|-------------------------------|---|------------------------------|------------------------------|---|
| • Adaptive Cruise Control | • Enhanced Automatic Emergency Braking | • Front and Rear Park Assist | • Lane Keep Assist | • Speed Limit Assist ³ |
| • Automatic Emergency Braking | • Following Distance Indicator ³ | • Front Pedestrian Braking | • Rear Cross Traffic Braking | • Traffic Sign Recognition ³ |
| • Blind Zone Steering Assist | • Forward Collision Alert | • HD Surround Vision | • Reverse Automatic Braking | |
| • Buckle to Drive | | • IntelliBeam | • Safety Alert Seat | |

*Exterior dimensions without mirrors.

**Payload value available with 11,000 lb. Gross Vehicle Weight Rating package.

1. GM estimate for a 250 mile range pack based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including temperature, terrain, battery age, loading, and how you use and maintain your vehicle.

2. Whichever comes first.

3. Feature may have late availability.

MY23 vehicle shown with aftermarket decals. MY24 vehicle subject to change.

BrightDrop has taken reasonable steps to ensure information presented is accurate. However, BrightDrop reserves the right to make changes to this without notice. Please consult the Vehicle Order Guide for the latest information.

Safety or driver assistance features are no substitute for the driver's responsibility to operate the vehicle in a safe manner. The driver should remain attentive to traffic, surroundings and road conditions at all times. Visibility, weather, and road conditions may affect feature performance. Read the vehicle Owner's Manual for more important feature limitations and information.

2024 Zevo 600 Specifications & Highlights



EXTERIOR	ZEVO 600 FWD	ZEVO 600 AWD
Wheelbase	183 in.	183 in.
Overall length	290 in.	290 in.
Overall width without mirrors	86.52 in.	86.52 in.
Overall width with mirrors	106.2 in.	106.2 in.
Overall height	108.87 in.	108.79 in.
Overall height with shark fin antenna	109 in.	109 in.
Overall height with mast antenna	117.57 in.	117.57 in.
Turning diameter, curb-to-curb	54.8 in.	53.2 ft.
Minimum ground clearance	7.51 in.	7.51 in.
Front overhang	33.99 in.	33.99 in.
Rear overhang	72.57 in.	72.57 in.
Curbside step, height to ground	15.49 in.	15.49 in.
Rear step bumper, height to ground	18.09 in.	18.02 in.
Approach angle	23.1 degrees	23.2 degrees
Departure angle, rear	12.6 degrees	12.6 degrees

INTERIOR	ZEVO 600 FWD	ZEVO 600 AWD
Internal cargo area height, door closed	82 in.	82 in.
Internal cargo area height, door open	76 in.	76 in.
Curbside door opening width	36.67 in.	36.67 in.
Bulkhead access dimensions with door open	75.81 in. H x 28.21 in. W	75.81 in. H x 28.21 in. W
Cargo floor, height to ground	26.39 in.	26.39 in.
CAPACITY	ZEVO 600 FWD	ZEVO 600 AWD
Cargo volume	614.7 cu. ft.	614.7 cu. ft.
Cargo area dimensions	168.8 in. L x 83.68 in. W x 82 in. H	168.8 in. L x 83.68 in. W x 82 in. H
Rear cargo access dimensions with door open	57.57 in. x 73.44 in.	57.57 in. x 73.44 in.
Base curb weight	7,700 lbs.	7, 919 lbs.
BATTERY	ZEVO 600 FWD	ZEVO 600 AWD
GM-estimated driving range on a full charge	Up to 200 miles ¹	250 miles ¹
Peak charge rate	Up to 160 mi./hr. of charging (120-kW DC Fast Charging ¹)	Up to 160 mi./hr. of charging (120-kW DC Fast Charging ¹)

1. GM estimate for a 250 mile range pack based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including battery pack size, temperature, terrain, battery age, loading, and how you use and maintain your vehicle.