

ZESBI Approved Product List

Zero Emission School Bus & Infrastructure

Approved Product List for Zero-Emission School Bus and Infrastructure (ZESBI) Project

Administered by the California Energy Commission

Last Updated: June 13, 2025



This document was prepared as a result of work funded through the California Energy Commission. It does not necessarily represent the views of the Energy Commission, its employees, or the State of California. The Energy Commission, the state of California, its employees, contractors, and subcontractors make no warranty, express or implied, and assume no legal liability for the information in this document; nor does any party represent that the use of this information will not infringe upon privately owned rights. This document is updated bimonthly.

ZESBI Approved Product List

Contents

Acronyms3

Criterion Definitions.....4

Charger Technical Requirements.....5

 All ZESBI EVSE:.....5

 Bidirectional DCFC:.....6

Level 2 and DCFC Approved Product List6

Vehicle to Grid Approved Product List.....37

ZESBI Approved Product List

Acronyms

Acronym	Description
AC	Alternating Current
APL	Approved Product List
CCS	Combined Charging System
CEC	California Energy Commission
DC	Direct Current
DCFC	Direct Current Fast Charger
EV	Electric Vehicle
EVSE	Electric Vehicle Supply Equipment
IOU	Investor Owned Utilities
ISO	International Organization for Standardization
kW	Kilowatts
NRTL	Nationally Recognized Testing Laboratory
OCA	Open Charge Alliance
OCPP	Open Charge Point Protocol
SAE	Society of Automotive Engineers
UL	Underwriters Laboratories
V2G	Vehicle to Grid
ZESBI	Zero-Emission School Bus and Infrastructure

ZESBI Approved Product List

Criterion Definitions

Category	Description
ISO-15118 Ready	International Organization for Standardization (ISO) -15118 Ready is an industry standard that outlines digital communication between electric vehicles (EVs) and chargers and is already widely used for direct current charging controls. More information may be found here .
ISO-15118-3	Powerline communication based digital communication.
ISO-15118-20 Ready	ISO-15118-20 Ready includes bidirectional charging and stronger cybersecurity requirements than that of previous iterations of ISO15118.
OCPP 2.0.1 Capable	Charger <u>is capable of operating with the Open Charge Alliance (OCA) Open Charge Point Protocol (OCPP) version 2.0.1.</u> , however is not yet integrated into the charger to date.
OCPP 2.0.1 Operational	Charger connects to a charging station management system and is <u>operational</u> with the OCA OCPP, version 2.0.1., however the charger <u>is not OCA OCPP certified</u> to date.
OCPP Certification Full 2.0.1	Network to EVSE connectivity is operated with <u>and is compliant with the OCA OCPP, version 2.0.1.</u>
OCPP Security 2.0.1	Network has completed certification with the OCA for Security Certification OCPP 2.0.1.
Rule 21	A tariff that describes the interconnection, operating and metering requirements for generation facilities to be connected to an investor-owned utility's distribution system and transmission system over which the California Public Utilities Commission has jurisdiction.
SAE J1772	Charger connector is compliant with Society of Automotive Engineers (SAE) J1772.
SAE J3400	Charger connector is compliant with SAE J3400.
SAE J1772 CCS	Charger connector is compliant with SAE 1772 Combined Charging System (CCS).
Underwriters Laboratory	Unit certified by qualified Nationally Recognized Test Laboratory.

ZESBI Approved Product List

Category	Description
Vehicle to Grid (V2G)	A charging technology that allows energy in an EV battery to be pushed back into the electrical grid. V2G is also commonly referred to as bidirectional charging because of the two-way flow of electrical energy.

Charger Technical Requirements

To be eligible for Zero-Emission School Bus and Infrastructure (ZESBI) incentives, an electric vehicle supply equipment (EVSE) must be on this ZESBI Approved Product List (APL) at the time the cost of the EVSE was incurred. See section 7.2 of the [California Energy Commission's \(CEC's\) ZESBI Implementation Manual](#) (IM) for more details.

For electric vehicle (EV) chargers using conductive connectors, only Level 2, direct current fast chargers (DCFC) and bidirectional DCFC are eligible for ZESBI funding. The minimum power level for an eligible Level 2 charger under ZESBI is 19.2 kilowatts (kW).

All ZESBI EVSE:

1. Must be safety certified by a Nationally Recognized Testing Laboratory (NRTL) recognized by the U.S. Occupational Safety and Health Administration (OSHA). [See OSHA's complete list of NRTLs](#).
2. Must include a standard charging connector or interface:
 - a. At least 50 percent of Level 2 chargers shall include, at a minimum, a Society of Automotive Engineers (SAE) J1772 connector.
 - i. The remaining 50 percent may include either SAE J1772 or SAE J3400 connectors.
 - b. At least 50 percent of DCFCs shall include, at a minimum, a SAE J1772/Combined Charging System 1 (CCS1) connector.
 - i. The remaining 50 percent may include either SAE J1772/CCS1 or SAE J3400 connectors.
3. Must be networked and support at a minimum:
 - a. Open Charge Point Protocol (OCPP) capable (EVSE installed after April 1, 2025, shall be certified for OCPP 2.0.1 or later).
 - b. Must be ISO 15118 Ready as defined in the CEC's [updated ISO 15118 recommendation](#).
 - i. Powerline communication based digital communication as specified in ISO 15118-3.
 - ii. Secure management and storage of keys and certificates using a hardware security module, SoftHSM, or similar technology.
 - iii. Transport Layer Security version 1.2.
 - iv. Remotely receiving updates to activate or enable ISO 15118 use cases.
 - v. Connecting to a charging station management system (i.e. OCPP).

ZESBI Approved Product List

- vi. Selecting the appropriate communication protocol requested by the EV.
- 4. Must have reasonable pricing and reflect current market rates.
- 5. Must include proper regulatory signs for chargers and parking facilities.

Bidirectional DCFC:

In addition to the above requirements, bidirectional DCFC (if selected):

- 1. Must be safety certified to UL 1741 Supplement B as a prerequisite for interconnection.
 - a. Applicants and Incentive Recipients must refer to the applicable Investor Owned Utility's (IOU) interconnection tariff (Rule 21) for the latest requirements, IOUs set their own requirements, please reach out to your utility for further details about Rule 21.
 - b. This requirement does not apply to solicitations that are funding bidirectional chargers strictly for off-grid backup purposes.
- 2. Must be ISO 15118-20 Ready. An EVSE is considered ISO 15118-20 Ready if capable of the following:
 - i. Powerline communication based digital communication as specified in ISO 15118-3.
 - ii. Secure management and storage of keys and certificates used with ISO 15118-2 and ISO 15118-20.
 - iii. Transport Layer Security version 1.3.
 - iv. Remotely receiving updates to activate or enable ISO 15118-20 use cases.
 - v. Connecting to a charging station management system (i.e. OCPP).
 - vi. Selecting the appropriate communication protocol requested by the EV.

Level 2 and DCFC Approved Product List

The following ZESBI APL has been created using the [Electric Power Research Institute \(EPRI\) Vetted Product List](#) and captures the minimum criteria* listed in the ZESBI Implementation Manual for Level 2 and DCFC. The EVSE/charger selected for the ZESBI Incentive Project must be listed within this APL at the time the cost of the EVSE is incurred. For more information about any of the chargers listed below and/or more details about the information within the "Specification Notes", please reach out to the charger brand/original equipment manufacturer. EVSE original equipment manufacturers may contact ZESBI staff for questions about the EVSE listed in this APL at schoolbusteam@calstart.org

***All EVSE installed after April 1, 2025, must be certified by the Open Charge Alliance (OCA) for OCPP 2.0.1 or later (compliant to Core (Subset) and Security Profile Certifications).**

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
ABB	A400	A400	DCFC	400	SAE J1772/CCS	Operational + Capable	Dual port. ISO 15118. Network Capable.
Alpitronic	HYC400-1	Hypercharger	DCFC	100	SAE J1772/CCS + J3400	Operational + Capable	1-4 Ports. ISO 15118. Network Capable.
Alpitronic	HYC400-2	Hypercharger	DCFC	200	SAE J1772/CCS + J3400	Operational + Capable	1-4 Ports. ISO 15118. Network Capable.
Alpitronic	HYC400-3	Hypercharger	DCFC	300	SAE J1772/CCS + J3400	Operational + Capable	1-4 Ports. ISO 15118. Network Capable.
Alpitronic	HYC400-4	Hypercharger	DCFC	400	SAE J1772/CCS + J3400	Operational + Capable	1-4 Ports. ISO 15118. Network Capable.
Alpitronic	HYC50	Hypercharger	DCFC	50	SAE J1772/CCS + J3400	Operational + Capable	1-2 Ports. ISO 15118. Network Capable.
Autel	Maxi UW19L002	MaxiCharger AC Pro 80A	Level 2	19.2	SAE J1772	Operational + Capable + Full Certificate + Security Certificate	Single port. ISO 15118. Fully Networked. Energy Star.
Autel	Maxi UW19C002	MaxiCharger AC Pro 80A	Level 2	19.2	SAE J1772	Operational + Capable + Full Certificate + Security Certificate	Single port. ISO 15118. Fully Networked. Energy Star.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	Level 2	19.2	SAE J1772	Operational + Capable + Full Certificate + Security Certificate	Single port. ISO 15118. Fully Networked. Energy Star.
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	Level 2	19.2	SAE J1772	Operational + Capable + Full Certificate + Security Certificate	Single port. ISO 15118. Fully Networked. Energy Star.
Autel	Maxi UW19LB02	MaxiCharger AC 80A	Level 2	19.2	SAE J1772	Operational + Capable + Full Certificate + Security Certificate	Single port. ISO 15118. Fully Networked. Energy Star.
Autel	DC HiPower	DC HiPower	DCFC	320	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Autel	DC HiPower	DC HiPower	DCFC	480	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	DC HiPower	DC HiPower	DCFC	640	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	DC Compact - UW040A2501	DC Compact	DCFC	40	SAE J1772/CCS	Operational + Capable	Dual Port.
Autel	UF####001	AC Ultra	Level 2	19.2	SAE J1772	Operational + Capable	Single Port or Dual Port. No credit card reader
Autel	UF####101	AC Ultra	Level 2	19.2	SAE J1772	Operational + Capable	Single Port or Dual Port

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Autel	UF060A3001	Maxicharger DC Fast 60kW	DCFC	60	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF080A3001	Maxicharger DC Fast 80kW	DCFC	80	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF100A3001	Maxicharger DC Fast 100kW	DCFC	100	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF120A3001	Maxicharger DC Fast 120kW	DCFC	120	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF140A4001	Maxicharger DC Fast 140kW	DCFC	140	SAE J1772/CCS	Operational + Capable	Single or dual port

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Autel	UF160A4001	Maxicharger DC Fast 160kW	DCFC	160	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DCFC	180	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DCFC	200	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DCFC	220	SAE J1772/CCS	Operational + Capable	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DCFC	240	SAE J1772/CCS	Operational + Capable	Single or dual port

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Blink	01-0577	Blink 120kW	DCFC	120	SAE J1772/CCS	Operational + Capable	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0578	Blink 180kW	DCFC	180	SAE J1772/CCS	Operational + Capable	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0568	Blink 300kW	DCFC	300	SAE J1772/CCS	Operational + Capable	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DCFC	360	SAE J1772/CCS	Operational + Capable	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
BTC Power	EVP-2001-80-#	L2W-80-240-##-###	Level 2	19.2	SAE J1772	Capable	ISO 15118. Fully Networked. Energy Star. Single port. BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
BTC Power	EVP-2002-80-#	L2P-80-240-##-###	Level 2	19.2	SAE J1772	Capable	ISO 15118. Fully Networked. Energy Star. Dual port. BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
CHAEVI	CV-3FD120P-IUL	SONIC (120 kW)	DCFC	120	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL	SONIC (150 kW)	DCFC	150	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180 kW)	DCFC	180	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	DCV-3FD120-ICN	DUOCONIC (120 kW)	DCFC	120	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150 kW)	DCFC	150	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180 kW)	DCFC	180	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	CV-3UD403P-NCC3	SUPERSONIC	DCFC	400	SAE J1772/CCS	Operational + Capable	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
ChargePoint	CP60##X-80A-L##	6000 Series	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Fully Networked. Energy Star. CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
ChargePoint	CPE250C-625-CCS1-200A-****	Express 250	DCFC	62.5	SAE J1772/CCS	Capable	ISO 15118. Fully Networked ChargePoint Express 250 Station (62.5 kW) - includes Express 250 Station, 2x Power Modules, 1x CCS1 200A cable, 1x CHAdeMO cable or NACS, North America Modem/SIM, cUL and UL listed, requires CPE250-CMT-IMPERIAL in US, CPE250-CMT-METRIC in Canada. CPE250-CMT-IMPERIAL/METRIC not included. FWHA and FTA compliant models available as well as with integrated EMV Chip Reader terminal.
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DCFC	160	SAE J1772/CCS	Capable	ISO 15118. Fully Networked. Energy Star. [Paired Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DCFC	80	SAE J1772/CCS	Capable	ISO 15118. Fully Networked. Energy Star. [Single Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DCFC	160	SAE J1772/CCS	Capable	ISO 15118. Fully Networked. Energy Star. [Paired Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DCFC	80	SAE J1772/CCS	Capable	ISO 15118. Fully Networked Energy Star. [Single Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DCFC	160	SAE J1772/CCS	Capable	ISO 15118. Fully Networked. Energy Star. [Paired Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DCFC	80	SAE J1772/CCS	Capable	ISO 15118. Fully Networked. Energy Star. [Single Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed,

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							FWHA and FTA compliant models available.
ChargePoint	Express Plus 1000 Power Block: CPPB0001*** PM1.5 43-001200-** EXPP-PL10##*-##*##- ##*##-***	Express Plus	DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Express Plus system includes Power Block, Power Modules, and Power Link 1000 series; Used for Fleet or Commercial.
ChargePoint	Express Plus 2000 (EXPP-PL20##)	Express Plus	DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##-CHIP)	Express Plus	DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. [CHIP sku]Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
ChargePoint	Express Plus 2000 (EXPP-PL20##-FHWA)	Express Plus	DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. [FHWA sku] Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
ChargeTronix	CTC-CAC80	FLUX AC	Level 2	19.2	SAE J1772	Operational + Capable	Single or double port.
ChargeTronix	CTX-C40-240-2	FLUX AC Dual 40A	Level 2	19.2	SAE J1772	Operational + Capable	Dual port.
ChargeTronix	CTX-C80-240-1	FLUX AC Single 80A	Level 2	19.2	SAE J1772	Operational + Capable	Single port.
ChargeTronix	CTX-C80-240-2	FLUX AC Dual 80A	Level 2	19.2	SAE J1772	Operational + Capable	Dual port.
ChargeTronix	CTX-AiO-60	Apex 60kW DCFC	DCFC	60	SAE J1772/CCS	Operational + Capable	Dual port.
ChargeTronix	CTX-AiO-120	Apex 120kW DCFC	DCFC	120	SAE J1772/CCS	Operational + Capable	Dual port.
ChargeTronix	CTX-AiO-160	Apex 160kW DCFC	DCFC	160	SAE J1772/CCS	Operational + Capable	Dual port.
ChargeTronix	CTX-AiO-240	Apex 240kW DCFC	DCFC	240	SAE J1772/CCS	Operational + Capable	Dual port.
ChargeTronix	"Power Cabinet: CTX-DSPB-480 Dispenser: CTX-DST"	Nexus 480kW Distributed System	DCFC	480	SAE J1772/CCS	Operational + Capable	Up to 6 ports.
ChargeTronix	"Power Cabinet: CTX-DSPB-360 Dispenser: CTX-DST"	Nexus 360kW Distributed System	DCFC	360	SAE J1772/CCS	Operational + Capable	Up to 6 ports.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Espen	EVC/D030/S###	EVC/D030/S###	DCFC	30	SAE J1772/CCS	Operational + Capable	ISO 15118. Network capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D060/S###	EVC/D060/S###	DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D120/S###	EVC/D120/S###	DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D180/S###	EVC/D180/S###	DCFC	180	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Espen	EVC/D360/S###	EVC/D360/S###	DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Power Cabinet. 1x CCS1 connector or 1x CHAdeMO connector. Vetted dispensers: DDWU362T0TE2PN-RW, DDWU362T0TE2N7-RW, DDWU362V00E2N7-RW, DDWU362U0UE2PN-RW, DDWU362U0UE2N7-RW, DDWU362K0TE2PN-RW, DDWU362K0TE2N7-RW, DDWU362K0UE2PN-RW, DDWU362K0UE2N7-RW, DDWU362G00E2PN-RW,

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							DDWU362G00E2N7-RW, DDWU362K00E2PN-RW, DDWU362K00E2N7-RW, DDWU362U00E2PN-RW, DDWU362U00E2N7-RW, DDWU362T00E2PN-RW, DDWU362T00E2N7-RW, DDWU362V0UE2PN-RW, DDWU362V0UE2N7-RW, DDWU362V0KE2PN-RW, DDWU362V0KE2N7-RW, DDWU362V0TE2PN-RW, DDWU362V0TE2N7-RW, DDWU362V00E2PN-RW.
EverCharge	EV002-80,E800-1001	EV02	Level 2	19.2	SAE J1772 + J3400	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Single Port, Standalone network capability
EVPassport	C6AM150XX	C6AM150XX	DCFC	150	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Standalone DCFC, no HPC needed, runs off its own power
EVPassport	C6AM90XX	C6AM90XX	DCFC	95	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Runs on 208 3P power, standalone DCFC
FLO	Ultra	Ultra	DCFC	320	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Dual port.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Ford Pro Charging	FPC-AC0080ZC-U##	Ford Pro AC Charging Station, Series 2	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Single Port NRTL Listed as EX-1193-1
Ford Pro Charging	FPC-AC0019ZC-U##		Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Single Port NRTL listed as LiteOn EX 1193 XXXX certified models
Ford Pro Charging	FPC-DC0060AA-U##		DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. Single or Dual Port 2x CCS1 connector . NRTL listed as Power Electronics NB060SU20
Ford Pro Charging	FPC-DC0120AA-U##		DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked. Energy Star. 2x CCS1 200A or 300A connector NRTL listed as Power Electronics NB120SU20
Gateway International 360	GW-EV4400-120/XXX	GW-EV4400-120/XXX	DCFC	120	SAE J1772/CCS	Operational + Capable	1x CCS1 connector 1x CHAdeMO connector
Gateway International 360	GW-EV4400-180/XXX	GW-EV4400-180/XXX	DCFC	180	SAE J1772/CCS	Operational + Capable	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Gateway International 360	GW-EV4400-360/XXX	GW-EV4400-360/XXX	DCFC	360	SAE J1772/CCS	Operational + Capable	"Power Cabinet. 1x CCS1 connector or 1x CHAdeMO connector.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							Vetted dispensers are DDWU362T0TE2PN-RW DDWU362T0TE2N7-RW, DDWU362V00E2N7-RW DDWU362U0UE2PN-RW, DDWU362U0UE2N7-RW, DDWU362K0TE2PN-RW, DDWU362K0TE2N7-RW, DDWU362K0UE2PN-RW, DDWU362K0UE2N7-RW, DDWU362G00E2PN-RW, DDWU362G00E2N7-RW, DDWU362K00E2PN-RW, DDWU362K00E2N7-RW, DDWU362U00E2PN-RW, DDWU362U00E2N7-RW, DDWU362T00E2PN-RW, DDWU362T00E2N7-RW, DDWU362V0UE2PN-RW, DDWU362V0UE2N7-RW, DDWU362V0KE2PN-RW, DDWU362V0KE2N7-RW, DDWU362V0TE2PN-RW, DDWU362V0TE2N7-RW, DDWU362V00E2PN-RW."
Gateway International 360	GW-EV4400-60/XXX	GW-EV4400-60/XXX	DCFC	60	SAE J1772/CCS	Operational + Capable	1x CCS1 connector 1x CHAdeMO connector
Gravity	GR-LH500CX		DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Gravity	GT-AH200XX		DCFC	200	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.
Gravity	GT-AV200XX		DCFC	200	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.
Gravity	GT-LAV500EX		DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.
Gravity	GT-LLH500EX		DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.
Gravity	GT-LV500CX		DCFC	500	SAE J1772/CCS	Operational + Capable	ISO 15118. Fully Networked.
i-charging	blueberry	BB50	DCFC	50	SAE J1772/CCS + J3400	Operational + Capable	Dual port
i-charging	blueberry CLUSTER	blueberry CLUSTER	DCFC	500	SAE J1772/CCS + J3400	Operational + Capable	Four ports. Simultaneous charging, Dynamic Power Allocation, 50 to 900 kW. 1 to 3 Power Units (cabinets) and up to 4 plugs in dispenser and satellites
i-charging	blueberry FUSION	blueberry FUSION	DCFC	150	SAE J1772/CCS + J3400	Operational + Capable	Dual port. Simultaneous charging, Dynamic Power Allocation, 50, 100 and 150kW available
i-charging	blueberry PLUS	PU 200 R2 / PU 300 R2	DCFC	500	SAE J1772/CCS + J3400	Operational + Capable	Four ports. Simultaneous charging, Dynamic Power Allocation, 50 to 900 kW. 1 to 3 Power Units (cabinets) and 1 Dispenser w 2 Plugs
InCharge Energy	ICE 30	ICE 30	DCFC	30	SAE J1772/CCS	Operational + Capable	Network capable
InCharge Energy	ICE 60	ICE 60	DCFC	60	SAE J1772/CCS	Operational + Capable	Network capable dual

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
InCharge Energy	ICE 120	ICE 120	DCFC	120	SAE J1772/CCS	Operational + Capable	Networked dual
InCharge Energy	ICE 180	ICE 180	DCFC	180	SAE J1772/CCS	Operational + Capable	Networked dual
InCharge Energy	ICE 480	ICE 480	DCFC	480	SAE J1772/CCS	Operational + Capable	Up to 4 dispensers
InCharge Energy	ICE 80 AC	ICE 80 AC	Level 2	80	SAE J1772	Operational + Capable	Networked
InCharge Energy	ICE Dual 80 AC	ICE Dual 80 AC	Level 2	80	SAE J1772	Operational + Capable	Networked dual
InCharge Energy	ICE 60 Wallbox	ICE 60 Wallbox	DCFC	60	SAE J1772/CCS	Operational + Capable	Networked dual
Ingeteam	RAPID 120	RAPID 120	DCFC	120	SAE J1772/CCS	Operational + Capable	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 150	RAPID 150	DCFC	150	SAE J1772/CCS	Operational + Capable	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 180	RAPID 180	DCFC	180	SAE J1772/CCS	Operational + Capable	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 60E	RAPID 60E	DCFC	60	SAE J1772/CCS	Operational + Capable	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 90	RAPID 90	DCFC	90	SAE J1772/CCS	Operational + Capable	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Integra Energy	IEV/D030/SXXX	IEV/D030/SXXX	DCFC	30	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Integra Energy	IEV/D060/SXXX	IEV/D060/SXXX	DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Integra Energy	IEV/D360/SXXX	IEV/D360/SXXX	DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Power Cabinet. 1x CCS1 connector or 1x CHAdeMO connector. Vetted dispensers are DDWU362T0TE2PN-RW DDWU362T0TE2N7-RW, DDWU362V00E2N7-RW DDWU362U0UE2PN-RW, DDWU362U0UE2N7-RW, DDWU362K0TE2PN-RW, DDWU362K0TE2N7-RW, DDWU362K0UE2PN-RW, DDWU362K0UE2N7-RW, DDWU362G00E2PN-RW, DDWU362G00E2N7-RW, DDWU362K00E2PN-RW, DDWU362K00E2N7-RW, DDWU362U00E2PN-RW, DDWU362U00E2N7-RW, DDWU362T00E2PN-RW, DDWU362T00E2N7-RW, DDWU362V0UE2PN-RW, DDWU362V0UE2N7-RW, DDWU362V0KE2PN-RW, DDWU362V0KE2N7-RW, DDWU362V0TE2PN-RW, DDWU362V0TE2N7-RW, DDWU362V00E2PN-RW.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Integra Energy	IEV/D120/SXXX	IEV/D120/SXXX	DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Integra Energy	IEV/D180/SXXX	IEV/D180/SXXX	DCFC	180	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
IoTecha	CCS-ACL2 / CCS-C80A	CCS-C80A-xyyy	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. Single Port. xx - cable length (15 or 25ft) yyy - LTE option
IoTecha	CCS-C80C	CCS-C80C-xyyy	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. Single Port. xx - cable length (15 or 25ft) yyy - LTE option
Jule (eCAMION)	Jule-100	Jule Charger 100	DCFC	100	SAE J1772/CCS + J3400	Operational + Capable	ISO 15118. Network Capable. DCFC that works with ESS w/ voltage range 650-800VDC
Jule (eCAMION)	Jule-200	Jule Charger 200	DCFC	200	SAE J1772/CCS + J3400	Operational + Capable	ISO 15118. Network Capable. DCFC that works with ESS w/ voltage range 650-800VDC

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Jule (eCAMION)	Jule-300	Jule Charger 300	DCFC	350	SAE J1772/CCS + J3400	Operational + Capable	ISO 15118. Network Capable. DCFC that works with ESS w/ voltage range 650-800VDC
Lincoln Electric	Velion 150	Velion	DCFC	150	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Single port.
LITE-ON	EX-1193-M	IC2 80A	Level 2	19.2	SAE J1772	Operational + Capable	Single port.
Loop Global	EVS-80A-L2-002	EV-Fleet	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. SAE J1772, Standalone network capability
Loop Global	EVS-FLASH-300-D01	Infinity Flash (with screen)	DCFC	300	SAE J1772/CCS + J3400	Full Certificate	ISO 15118. Fully Networked. Dual port. Power cabinet required: EVS-FLASH- 360-PC01
Nuvve	TP-30DC-V1G-H1-C	30kW DCFC V1G	DCFC	30	SAE CCS	Capable	V1G, 1 port, Network Capable
Nuvve	TP-60DC-V1G-H1-C	60kW DCFC V1G	DCFC	60	SAE CCS	Capable	V1G, 1 port, Network Capable
Nuvve	TP-120DC-V1G-H1-C	120kW DCFC V1G	DCFC	120	SAE CCS	Capable	V1G, 1 port, Network Capable
Nuvve	TP-120DC-V1G-H2-CC	120kW DCFC V1G	DCFC	120	SAE CCS	Capable	V1G, 2 ports, Network Capable

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Nuvve	TP-160DC-V1G-H2-CC	160kW DCFC V1G	DCFC	160	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-180DC-V1G-H2-CC	180kW DCFC V1G	DCFC	180	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-200DC-V1G-H2-CC	200kW DCFC V1G	DCFC	200	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-240DC-V1G-H2-CC	240kW DCFC V1G	DCFC	240	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-300DC-V1G-H2-CC	300kW DCFC V1G	DCFC	300	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-360DC-V1G-H2-CC	360kW DCFC V1G	DCFC	360	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	TP-380DC-V1G-H2-CC	380kW DCFC V1G	DCFC	380	SAE CCS	Capable	V1G, 2 ports, Network Capable
Nuvve	JT-30DC-V1G	30kW DCFC V1G	DCFC	30	SAE CCS	Capable	V1G, 1 port, Network Capable
Nuvve	EVSE-B-P1-H1	PowerPort Neo	Level 2	19.2	SAE J1772	Capable	V1G, 1 port, Network Capable
OpConnect	IC80	IC80	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. Single Port NRTL Listed as EX-1193-1
OpConnect	SC80	SC80	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. Single Port NRTL Listed as EX-1193-3
SK Signet	PC600K-PS-##	PC600K-PS-##	DCFC	600	SAE J1772/CCS	Operational + Capable	This is distributed system that can connect up to two 400kW dispensers(Model no: DP400K-xx-PS-yy)

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							## : Variable based on any other options xx : Variable based on connector type(CCS1, NACS) yy : variable based on any other options
SK Signet	CD40*# / CP60*#	V2 VE 600kW Distributed system	DCFC	400	SAE J1772/CCS	Operational + Capable	Two dispensers type or four dispensers type. CCS1 and NACS connectors are supported. "*#" in the end of model number identifies any changes including hardware, option, certifications, and etc.
SK Signet	FC200K-##-##	V2 200kW AIO system	DCFC	200	SAE J1772/CCS	Operational + Capable	"xx" in the model number identifies connector type. "B2": Dual CCS1 connector "BH": CCS1 and NACS connector
SWTCH Energy	EX-1193-3	SWTCH Lite-On Platinum SC3 80A	Level 2	19.2	SAE J1772	Operational + Capable	ISO 15118. Network Capable. Energy Star. Single Port NRTL Listed as EX-1193-3
TECO-Westinghouse	DOWU362	Nexe VersaCharge 120kW	DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Power Cabinet. 1x CCS1 connector or 1x CHAdeMO connector. Vetted dispensers are DDWU362T0TE2PN-RW DDWU362T0TE2N7-RW, DDWU362V00E2N7-RW DDWU362U0UE2PN-RW,

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCP 2.0.1	Specification Notes
							DDWU362U0UE2N7-RW, DDWU362K0TE2PN-RW, DDWU362K0TE2N7-RW, DDWU362K0UE2PN-RW, DDWU362K0UE2N7-RW, DDWU362G00E2PN-RW, DDWU362G00E2N7-RW, DDWU362K00E2PN-RW, DDWU362K00E2N7-RW, DDWU362U00E2PN-RW, DDWU362U00E2N7-RW, DDWU362T00E2PN-RW, DDWU362T00E2N7-RW, DDWU362V0UE2PN-RW, DDWU362V0UE2N7-RW, DDWU362V0KE2PN-RW, DDWU362V0KE2N7-RW, DDWU362V0TE2PN-RW, DDWU362V0TE2N7-RW, DDWU362V00E2PN-RW.
TECO- Westinghouse	DSWU122	Nexe VersaCharge 180kW	DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DSWU182	Nexe VersaCharge 60kW	DCFC	180	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DSWU601	Nexe VersaCharge 90kW	DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
TECO-Westinghouse	DSWU901		DCFC	90	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
TECO-Westinghouse	DWWU301/DW30		DCFC	30	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Tellus Power	TP-EVPD-160kW		DCFC	160	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version 230202.2346
Tellus Power	TP-EVPD-180kW		DCFC	180	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector
Tellus Power	TP-EVPD-300kW		DCFC	300	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO
Tellus Power	TP-EVPD-360kW		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO
TurnOnGreen	FSP1200/CPEVDC-120KW-#	FSP1200	DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Single Port, CCS connector
TurnOnGreen	FSP300/CPEVDC-30KW-#	FSP300	DCFC	30	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Single Port, CCS connector
TurnOnGreen	FSP600/CPEVDC-60KW-#	FSP600	DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Single Port, CCS connector
Wallbox	DCF3-3*[x]-8[yyyyyy]-[zzz]	Supernova	DCFC	180	SAE J1772/CCS	Operational + Capable	Dual port. * = 0 is 180kW max model, 1 is 120kW max model, 2 is 60kW max model; [x]: one digit

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							numeric 0-9; [yyyyyyy]: seven digits numeric 0-9; [zzz]: three digits alphanumeric 0-9 and/or A-F Energy Star expected Q4'2024. CTEP/NTEP expected Q4'2024. NACS expected Q1'2025.
XCharge	C6AM150XX	C6AM150XX	DCFC	150	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Standalone DCFC, no HPC needed, runs off its own power
XCharge	C6AM90XX	C6AM90XX	DCFC	95	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Runs on 208 3P power, standalone DCFC
XCharge	C6AM200XX	C6AM200XX	DCFC	200	SAE J1772/CCS + J3400	Operational + Capable	Dual port.
XCharge	C7AM-240-CC / C7AM-240-LQ-CC	C7AM	DCFC	240	SAE J1772/CCS + J3400	Operational + Capable	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
XCharge	C7AM-280-CC / C7AM-280-LQ-CC	C7AM	DCFC	280	SAE J1772/CCS + J3400	Operational + Capable	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
XCharge	C7AM-320-CC / C7AM-320-LQ-CC	C7AM	DCFC	320	SAE J1772/CCS + J3400	Operational + Capable	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
XCharge	C7AM-360-CC / C7AM-360-LQ-CC	C7AM	DCFC	360	SAE J1772/CCS + J3400	Operational + Capable	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
XCharge	C7AM-400-CC / C7AM-400-LQ-CC	C7AM	DCFC	400	SAE J1772/CCS + J3400	Operational + Capable	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
Zerova	DDWU362G00####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362K00####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362K0T####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362K0U####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362T0T####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362U00####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362U0U####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DOWU362		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. Power Cabinet. 1x CCS1 connector or 1x CHAdeMO connector. Vetted dispensers are DDWU362T0TE2PN-RW DDWU362T0TE2N7-RW, DDWU362V00E2N7-RW DDWU362U0UE2PN-RW, DDWU362U0UE2N7-RW, DDWU362K0TE2PN-RW, DDWU362K0TE2N7-RW, DDWU362K0UE2PN-RW, DDWU362K0UE2N7-RW,

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
							DDWU362G00E2PN-RW, DDWU362G00E2N7-RW, DDWU362K00E2PN-RW, DDWU362K00E2N7-RW, DDWU362U00E2PN-RW, DDWU362U00E2N7-RW, DDWU362T00E2PN-RW, DDWU362T00E2N7-RW, DDWU362V0UE2PN-RW, DDWU362V0UE2N7-RW, DDWU362V0KE2PN-RW, DDWU362V0KE2N7-RW, DDWU362V0TE2PN-RW, DDWU362V0TE2N7-RW, DDWU362V00E2PN-RW.
Zerova	DDWU362V00####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362V0K####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362V0T####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DDWU362V0U####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.

ZESBI Approved Product List

Brand	Model Number	Model Name	Charger Type	Maximum Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
Zerova	DDWU362V0V####_##		DCFC	360	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star.
Zerova	DQWA242	DQ240	DCFC	240			
Zerova	DQWA360	DQ360	DCFC	360			
Zerova	DQWA482	DQ480	DCFC	480			
Zerova	DSWU122	ICS DS120	DCFC	120	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Zerova	DSWU182	ICS DS180	DCFC	180	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. 1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Zerova	DSWU601	ICS DS60	DCFC	60	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Zerova	DSWU901		DCFC	90	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector
Zerova	DWWU301/ DW30	ICS DW30	DCFC	30	SAE J1772/CCS	Operational + Capable	ISO 15118. Network Capable. Energy Star. 1x CCS1 connector 1x CHAdeMO connector

ZESBI Approved Product List

Vehicle to Grid Approved Product List

The following ZESBI APL has been created using the [EPRI Vetted Product List](#) and the CEC's [Vehicle-to-Grid \(V2G\) Equipment List](#), and captures the minimum criteria listed in the [CEC's ZESBI IM](#). The EVSE selected for the ZESBI Incentive Project must be listed within this APL at the time the cost of the EVSE is incurred. For more information about any of the chargers listed below and/or more details about the information within the "Specification Notes", please reach out to the charger brand/original equipment manufacturer.

EVSE original equipment manufacturers may contact ZESBI staff for questions about the EVSE listed in this APL at schoolbusteam@calstrart.org.

***If a bidirectional DCFC is selected, the Incentive Recipient is not required to participate in utility exporting events such as Emergency Load Reduction Programs (ELRP), ELRP may be utilized at the Incentive Recipient's discretion. Please see the Section above "[Bidirectional](#)" for more information.**

Brand	Model Number	Model Name	Type	Max Power Output (kW)	Connector Type	OCPP 2.0.1	Specification Notes
InCharge Energy	ICE 22 V2X	ICE 22 V2X	DCFC V2G	22	SAE CCS	Capable	V2G
InCharge Energy	ICE 44 V2X	ICE 44 V2X	DCFC V2G	44	SAE CCS	Capable	Networked V2G
Nuvve	TP-20DC-V2G-H1-C	20kW DCFC V2G	DCFC V2G	20	SAE CCS	Capable	V2G, 1 port, Network Capable
Nuvve	TP-40DC-V2G-H1-C	40kW DCFC V2G	DCFC V2G	40	SAE CCS	Capable	V2G, 1 port, Network Capable
Nuvve	TP-60DC-V2G-H1-C	60kW DCFC V2G	DCFC V2G	60	SAE CCS	Capable	V2G, 1 port, Network Capable

ZESBI Approved Product List

Tellus Power Green	TP-V2G-20-480		DCFC V2G	20	SAE CCS	Operational + Capable	UL 1741-SA certified. Bidirectional charger
Tellus Power Green	TP-V2G-30-480		DCFC V2G	30	SAE CCS	Operational + Capable	UL 1741-SA certified. Bidirectional charger
Tellus Power Green	TP-V2G-40-480		DCFC V2G	40	SAE CCS	Operational + Capable	UL 1741-SA certified. Bidirectional charger
Tellus Power Green	TP-V2G-60-480		DCFC V2G	60	SAE CCS	Operational + Capable	UL 1741-SA certified. Bidirectional charger