

XOS

SV

100% Battery-Electric



2026 XOS STEPVAN

XOS SV Stepvan

| | 4-Pack Battery Pack Configuration | 8-Pack Battery Pack Configuration |
|------------------------------|-------------------------------------|-------------------------------------|
| Classification | | |
| Model | 2026 SV | 2026 SV |
| Class | 5 - 6 | 5 - 6 |
| Wheel Configuration | 4x2 | 4x2 |
| General Dimensions* | | |
| Body Size - ft. | 16 - 22 | 16 - 22 |
| Vehicle Width - in. | 93" (interior) 95" (exterior) | 93" (interior) 95" (exterior) |
| Vehicle Height - in. | 116 - 124" | 116 - 124" |
| Cargo Volume - cu. ft. | 727 - 1,163 | 727 - 1,163 |
| Wheelbase - in. | 178", or 208" | 178", or 208" |
| Front Tires | 245/70R19.5 Optional 265/70R19.5 | 245/70R19.5 Optional 265/70R19.5 |
| Rear Tires | 245/70R19.5 | 245/70R19.5 |
| Front Wheels - in. | 19.5 x 6.75 | 19.5 x 6.75 |
| Rear Wheels - in. | 19.5 x 6.75 | 19.5 x 6.75 |
| Weight | | |
| Max Payload - lbs. | 7210 - 13,710 | 4650 - 11,150 |
| Curb Weight - lbs. | ~12,290 | ~14,850 |
| GVWR - lbs. | 19,500 - 26,000 | 19,500 - 26,000 |
| GAWR Front - lbs. | 9,000-10,000 | 9,000-10,000 |
| GAWR Rear - lbs. | 16,000 | 16,000 |
| Performance | | |
| Top Speed | 70 mph | 70 mph |
| Max Range - mi. | 100** | 200** |
| Max Horsepower - Hp | 347 | 347 |
| Max Torque - ft. - lbs. | 1,737 | 1,737 |
| Continuous Horsepower - Hp | 258 | 258 |
| Continuous Torque - ft. lbs. | 730 | 730 |
| Operating Temperature | -40°C - 85°C | -40°C - 85°C |

*Actual vehicle dimensions may vary depending on vehicle customization

**Actual vehicle range depends on vehicle load, environmental conditions, and driver behavior

***Charge times may vary depending on the charger used. The DC charge times here are calculated for a 60 kW DC charger. The AC charge times here are calculated for a 19.2 kW AC charger.

| | 4-Pack Battery Pack Configuration | 8-Pack Battery Pack Configuration |
|-----------------------------------|---|---|
| Powertrain | | |
| Powertrain | Central Drive | Central Drive |
| Propulsion | Direct-Drive | Direct-Drive |
| Motor | TM4 Sumo | TM4 Sumo |
| Front Axle and Equipment | | |
| Front Axle | Hendrickson 10K | Hendrickson 10K |
| Front Brakes | Hydraulic Disc | Hydraulic Disc |
| Front Suspension | Steel Leaf Spring | Steel Leaf Spring |
| Power Steering | Hydraulic | Hydraulic |
| Rear Axle and Equipment | | |
| Rear Axle | Dana S130 | Dana S130 |
| Rear Axle Ratio | 5.13 | 5.13 |
| Rear Brakes | Hydraulic Disc | Hydraulic Disc |
| Rear Suspension | Steel Leaf Spring | Steel Leaf Spring |
| Differential Lock | Open Differential | Open Differential |
| Charging | | |
| Charging Port Type | CCS1 Connector & J1772 Connector Components | CCS1 Connector & J1772 Connector Components |
| Battery Capacity - kWh | 140 | 280 |
| Time to Charge DC 0-80% | 2 hours*** | 4 hours*** |
| Time to Charge DC 0-100% | 3 hours*** | 6 hours*** |
| Time to Charge AC 0-80% | 6 hours*** | 12 Hours *** |
| Time to Charge AC 0-100% | 7.5 hours*** | 15 Hours *** |
| Max DC Charge Rating - kW | 124 | 124 |
| Max AC Charge Rating - kW | 19.2 | 19.2 |
| High-Voltage System Rated Voltage | 613 (nominal) 705 (max) | 613 (nominal) 705 (max) |
| Accessory Batteries | 12V and 24V (two 12V in series) | 12V and 24V (two 12V in series) |