



TRUCKS

A Toyota Group Company

Le | SERIES

ELECTRIC TRUCKS

MY27 L6e/L7e

**MORE THAN
A TRUCK**



THE EVOLUTION OF CONNECTIVITY.

Hino Edge is a powerful, next-generation connected vehicle solution, included at no charge for the first 5 years and standard on all Hino trucks. It gives fleets real-time visibility into vehicle location and performance, proactive vehicle health monitoring with fault alerts, a simplified service experience through direct case communication, and integrated telematics to help keep trucks on the road and businesses moving.



Le | SERIES

ELECTRIC TRUCKS

MY27 L6e/L7e



MOTOR/DRIVETRAIN/AXLE

Accelerera Integrated eAxle 14Xe Gen 4.5	
Peak Power	260 kW / 348 hp
Continuous Power	180 kW / 241 hp
Transmission	Integrated Two-Speed Automatic

BATTERIES & HV SYSTEM

HV Battery System	Hexagon Purus ProPack™
Battery Cell	Panasonic Energy Lithium Ion
Battery Capacity (Total / Usable)	269 kWh / 238 kWh
System Voltage	750V Max System Voltage
DC Fast Charging	Up To 120kW
DC Charger Type	CCS Type 1
AC Level 2 Charging	80 Amp 240V Level 2 Charging 19.2 kW
Charging Time (MAX DC)	1.8 Hours (0-80% SOC @ 120 kW)
Charging Time (MAX AC)	9.2 Hours (0-80% SOC @ 19.2 kW)

RATINGS & CAPACITIES

GVWR	25,950 Lbs. / 33,000 Lbs.
Service Brake System Type	Air Bendix ADB22X 22.5 in. ConMet Disc
Front Axle	Dana Spicer E-Series E-1202W 12,500 Lbs.
Rear Axle	23,000 Lbs.
Front & Rear Tires	Bridgestone Rib 11R22.5 R268FZ G-Load
Frame Yield Strength	.354x10.16x3.50 in, 120Kpsi (RBM 1,877,214/Rail)

POPULAR OPTIONAL EQUIPMENT

Back-up alarm
Mirrors, single arm fender mounted, outside rearview, power heated - chrome or black
Convex passenger side look down mirror
Power windows and door locks (with or without keyless entry)

*Not all equipment combinations are compatible. For compatibility, additional options and specifications please visit your local Authorized Hino Trucks Dealer. Are you a body company? Additional information @ hinobodybuilder.com

Legal Disclaimer - The equipment and specifications shown are subject to change without notice. The information, content, and materials are presented "as is" at the time of publication, and no representations are made that the content is error-free. ©Hino Motors Sales U.S.A., Inc. All rights reserved. All other marks are trademarks of their respective owners.

ELECTRICAL & SAFETY

Low Voltage System Maintenance Smart-Awake Active 12V Management	
HV Safety Continuous HVIL + Emergency Active Discharge	
Wabco 4S/4M ABS with Automatic Traction Control and Electronic Stability Control, Advanced Electronic Braking System (ZF OnGuardMax)	
Driver And Passenger 3-Point Seat Belt, Black	

CAB & CHASSIS

Cab Type	Galvanized Steel Reinforced Two Door Day Cab
Wheelbase	253.00 in. / 271.00 in.
BBC	109.6in
Cab to Axle/Trunnion	185.5 / 203.8 in.

STANDARD FEATURES

Bendix Air Disc Brakes	ADB22X
Air Dryer	Bendix AD-IS Air Dryer
Gear Selection	Push Button Electronic Shift Selector - Dash mounted
Driver's Seat	National 4-Way Adjustable High Back Vinyl Air Suspension RH Arm Rest
Passenger's Seat	CVG 2/3 Width Vinyl Two Man Bench
Tow Hooks	LH And RH Frame Mounted Front Hooks
Regenerative Braking	10 Selectable Levels
Collision Mitigation System	ZF OnGuardMAX

WHAT TO EXPECT

Smooth Automotive Feel, Effortless Power	
Chassis Weight (pre-body): 13,840 Lbs.	
Nearly Clear Frame Rails Back of Cab for Easy Upfit Options	
Unparalleled Visibility	

SERVICES



Hexagon Purus ProPack™	HV Battery & EV System	3 yrs/150k Miles/350 Mh of Discharge
Accelerera	eAxle 14Xe Gen 4.5	2 yrs/200k Miles
HINO EDGE	Telematics	STD 5 Year
HINOWATCH	24/7 Roadside Assistance	STD 3 Year

